

HPE ProLiant DL345 Gen11

What's new

- Powered by the 4th Generation AMD EPYC™ Processors with 5nm technology that supports up to 128 cores at 400W, 384 MB of L3 cache, and 12 DIMMs for DDR5 memory up to 4800 MT/s.
- 12 DIMM channels per processor for up to 3 TB total DDR5 memory with increased memory bandwidth and performance, and lower power requirements.
- Advanced data transfer rates and higher network speeds from the PCIe Gen5 serial expansion bus, with up to 6x16 PCIe Gen5, two OCP 3.0 slots, and up to 36 EDSFF E3S 1T NVMe.
- Includes HPE Integrated Lights-Out 6 (iLO 6) server management software that enables you to securely configure, monitor, and update your HPE ProLiant Gen11 servers seamlessly from anywhere.
- Supports hot-pluggable, high-availability RAID M.2 boot options.
- Supports mid/rear drive bay options, total of up to 34 SFF / 20 LFF drives.

Overview

Are you looking for a single-socket scalable server solution to power your virtualized data-intensive, large-capacity storage workloads?

The HPE ProLiant DL345 Gen11 server is a scalable 2U 1P solution that delivers exceptional compute performance and large capacity storage options at 1P economics. Powered by 4th Generation AMD EPYC™ Processors with up to 128 cores, increased memory bandwidth (up to 3 TB), high-speed PCIe Gen5 I/O and EDSFF storage, up to 20 LFF/ 34 SFF/ 36 EDSFF, and up to four GPUs at the front[1], this server is a superb single-socket 2U solution for your data-intensive workloads. Enhanced security features with the silicon root of trust from HPE are built into the firmware, creating a digital fingerprint for the AMD Secure Processor to validate safe operation prior to boot. The HPE ProLiant DL345 Gen11 server provides impressive storage performance and options for data-intensive workloads such as software-defined storage, video transcoding, and virtualized apps.

Features

Intuitive Cloud Operating Experience: Simple, Self-service, and Automated

HPE ProLiant DL345 Gen11 servers are engineered for your hybrid world. The HPE ProLiant Gen11 servers simplify the way you control your business's compute—from edge to cloud—with a cloud operating experience.

Transform business operations and pivot your team from reactive to proactive with global visibility and insight through a self-service console.

Automate tasks for efficiency in deployment and instant scalability for seamless, simplified support and lifecycle management, reducing tasks and shortening maintenance windows.

These experiences are engineered and built into all HPE ProLiant Gen11 servers, whether purchased as physical servers or consumed as-a-service using HPE GreenLake as your compute and storage demands grow.

Simplify and secure server management from edge to cloud with HPE GreenLake for Compute Ops Management. HPE GreenLake for Compute Ops Management is an as-a-service compute management experience that delivers greater simplicity, agility, and speed across your entire compute landscape.

globally.

Trusted Security by Design: Uncompromising, Fundamental, and Protected

The HPE ProLiant DL345 Gen11 server is tied into the silicon root of trust and the AMD Secure Processor, a dedicated security processor embedded in the AMD EPYC™ system on a chip (SoC), to manage secure boot, memory encryption, and secure virtualization.

HPE ProLiant Gen11 servers use the silicon root of trust to anchor the firmware of an HPE ASIC, creating an immutable fingerprint for the AMD Secure Processor that must be matched exactly before the server will boot. This helps ensure malicious code is contained, and healthy servers are protected.

HPE ProLiant Gen11 servers continuously protect healthy servers at the edge by providing rapid detection of security-compromised servers, even to the point of not allowing them to boot if it identifies and contains malicious code, with iDevID certificates installed by default.

HPE ProLiant Gen11 servers provide automated recovery from a security event, including restoration of validated firmware, and facilitating recovery of the operating system, application, data connections, and providing a fast path to bring a server back online and into normal operations.

From silicon to software, from factory to cloud, and from generation to generation, HPE ProLiant Gen11 is engineered with a fundamental security approach to defend against increasingly complex threats through an uncompromising commitment to constant security advancements that are built into our DNA.

Customized Performance for your Workloads: Accelerated, Open, and Efficient

The HPE ProLiant DL345 Gen11 server is an excellent choice for data-intensive workloads such as software-defined storage, video transcoding, and such, and virtualized apps that require large storage capacity, and high I/O and memory bandwidth.

Harness major computer performance. The HPE ProLiant DL345 Gen11 server is powered by the 4th Generation AMD EPYC™ Processors with 5nm technology that supports up to 128 cores, 400W, and 384 MB of L3 cache.

Advanced data transfer rates and higher network speeds from the PCIe Gen5 serial expansion bus, with up to 6x16 PCIe Gen5 and two OCP slots, improve I/O throughput and reduce latency.

Increase memory bandwidth and performance, and lower power requirements with 12 DIMM channels per processor for up to 3 TB total DDR5 memory.

Provide real-time operational feedback on server performance plus recommendations for fine-tuning BIOS settings to customize for changing business needs.



Technical specifications

HPE ProLiant DL345 Gen11

Processor type	AMD
Processor family	4th Generation AMD EPYC™ Processors
Processor number	1
Processor core available	Up to 128, depending on processor
Processor cache	Up to 384 MB L3 cache, depending on processor model
Processor speed	4.0 GHz maximum, depending on processor
Power supply type	2 Flexible Slot power supplies maximum, depending on model
Expansion slots	8 maximum, for detailed descriptions refer to the QuickSpecs
Maximum memory	3.0 TB with 256 GB DDR5
Memory slots	12
Memory type	HPE DDR5 Smart Memory
Memory protection features	ECC
System fan features	6 fans included
Network controller	Optional OCP and/or optional PCIe Network adapters, depending on model
Storage controller	HPE Smart Array SAS/SATA Controllers or Tri-Mode controllers, refer to the QuickSpecs for more details
Infrastructure management	HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download), HPE iLO Advanced, HPE iLO Advanced Premium Security Edition, and HPE OneView Advanced (require licenses), HPE GreenLake for Compute Ops Management (subscription included)
Warranty	3/3/3: Server Warranty includes three years of parts, three years of labor, and three years of on-site support coverage. Additional information regarding worldwide limited warranty and technical support is available at: https://support.hpe.com/hpsc/wc/public/home . Additional HPE support and service coverage for your product can be purchased locally. For information on availability of service upgrades and the cost for these service upgrades, refer to the HPE website at https://www.hpe.com/support .
Drive supported	8 or 12 LFF SAS/SATA with 4 LFF mid drives and 4 LFF rear drives optional 8 or 16 or 24 SFF SAS/SATA/NVMe with 8 SFF mid drives and 2 SFF rear drives optional 36 EDSFF E3.S 1T NVMe



GPUs chassis support available in Q3 2023. Subject to change.



For additional technical information, available models and options, please reference the [QuickSpecs](#)

**Make the right purchase decision.
Contact our presales specialists.**

[Find a partner](#)



© Copyright 2023 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

AMD EPYC™ is a trademark of Advanced Micro Devices, Inc. All third-party marks are property of their respective owners.

Image may differ from the actual product [PSN1014689145IEEN](#), September, 2023.